



SHALEDRILLER 164

DRAWWORKS

1,000 HP American Block Drawworks powered by (1) 1,000 HP AC Motor

MAST AND SUBSTRUCTURE

Vertically-Erecting Telescoping Mast: 136' Height, 500,000 lbs. Static Hook Load Hydraulically Raised Parallelogram Substructure: Floor Height 20' Clear Height 16'7"

Setback Capacity: 350,000 lbs.

Racking Capacity: 15,000' (5" Drill Pipe)

Fully integrated, omnidirectional "Walking" System

MUD PUMPS

(2) 1,600 HP Triplex Pumps - 5,000 psi (1) each 1,500 HP AC Motor

ROTATING AND TRAVELING EQUIPMENT

275 ton Canrig 6027 Top Drive w/ 30,000 ft-lbs. torque @ 110 rpm 27-1/2" Rotary Table Independent Drive powered by (1) Hydraulic Motor (rotary not suited for drilling application "false rotary") 250 ton Traveling Block

B.O.P. EQUIPMENT

BOP Handling System: Trolly Beam System w/ Manual Winches 13-5/8" x 5,000 psi, Annular 13-5/8" x 5,000 psi, Double Ram BOP 2-1/16" X 4-1/16" 5,000 psi, Choke Manifold (1) 7 Station Accumulator Skid

GENERATORS

(3) CAT 3512C Diesel Engines w/ (3) 1950 kVa Generator Sets

CONTROL SYSTEM

IEC VFD House

Climate Control Driller's Cabin w/ joystick controls





SHALEDRILLER 164 (continued)

MUD SYSTEM

1000 bbl. Pit System - 5,000 psi

- (3) MI Swaco Venom Shale Shakers
- (1) Vacuum Degasser
- (1) Mud Gas Separator 1,200 gpm 48" diameter / 16' overall length
- All solids Control Equipment mount on a one load hydraulically raised equipment skid

MUD MIXING EQUIPMENT

(1) Chemical Mixing Hopper on a single skid

LIQUID STORAGE

- (1) 440 bbl. Water Storage Tank
- (1) 250 bbl. Diesel Storage Tank

PIPE HANDLING EQUIPMENT

- (1) FH-80 Iron Roughneck
- (1) Forum Hydraulic Catwalk

ELECTRONIC DRILLING RECORDING EQUIPMENT

MD Totco Recording System and Equipment

DRILL PIPE

15,000' - 5" (S-135) 19.50# w/ NC-50 Connections

DRILL COLLARS

(20) 6.5" w/ NC-46 Connections (5) 8" w/ NC-56 Connections

LIVING QUARTERS

- (1) Rig Manager trailer
- (2) Twelve Person Crew Trailers
- (1) Change House washer, dryer and crew lockers