



SHALEDRILLER 230

DRAWWORKS

1,500 HP AMC Drawworks powered by (1) 1,500 HP AC Motor

MAST AND SUBSTRUCTURE

Hydraulically Telescoping, three (3) Section Mast: 136' Height, 750,000 lbs. Static Hook Load Hydraulically Raised "Two Section" Substructure: 31' Height w/ 6' skid beam , 20' Clear Height Setback Capacity: 500,000 lbs. Racking Capacity: 20,000' (5" Drill Pipe) Fully independent, omnidirectional "Walking" system

MUD PUMPS

(3) 1,600 HP Triplex Pumps - 7,500psi (1) each 1,500 HP AC Motor

ROTATING AND TRAVELING EQUIPMENT

500 ton Canrig 1250 Top Drive w/ 51,400 ft-lbs. torque @ 118 rpm 37-1/2" Rotary Table Independent Drive powered by (1) 1,000 HP AC Traction Motor 400 ton Traveling Block

B.O.P EQUIPMENT

BOP Handling System: Trolly Beam System w/ Manual Winches 13-5/8" x 5,000 psi Annular 13-5/8" x 10,000 psi, Single Ram BOP 13-5/8" x 10,000 psi, Double Ram BOP 2-1/16" X 4-1/16" 10,000 psi Choke Manifold (1) 7 Station Accumulator Skid

GENERATORS

(3) CAT 3512C Diesel Engines w/ (3) 1750 kVa Generator Sets

CONTROL SYSTEM

VFD House Climate Control Driller's Cabin w/ joystick controls





SHALEDRILLER 230 (continued)

MUD SYSTEM

1000 bbl. Pit System - 7,500 psi

(3) Derrick Hyperpool Shale Shakers

(1) Brandt 16 Cone Desilter

- (1) Vacuum Degasser
- (1) Mud Gas Separator 1,200 gpm 60" diameter / 21'7" overall length

MUD MIXING EQUIPMENT

(2) Chemical Mixing Hoppers(1) Caustic Mixing System

LIQUID STORAGE

(1) 500 bbl. Water Storage Tank(1) 500 bbl. Diesel Storage Tank

PIPE HANDLING EQUIPMENT

(1) FH-80 Iron Roughneck(1) Forum Hydraulic Catwalk

ELECTRONIC DRILLING RECORDING EQUIPMENT

MD Totco Recording System and Equipment

DRILL PIPE

20,000' - 5" (S-135) 19.50# w/ NC-50 Connections (30) Joints - 5" HWDP

DRILL COLLARS

(18) 6.5" w/ NC-46 Connections(6) 8" w/ NC-56 Connections

LIVING QUARTERS

(1) Rig Manager Trailer

- (2) Twelve Person Crew Trailers
- (1) Change House—washer, dryer and crew lockers