



SHALEDRILLER 303

DRAWWORKS

1,500 HP American Block Drawworks powered by (1) 1,500 HP AC Motor

MAST AND SUBSTRUCTURE

Cantilever Type, three (3) Section Mast: 142' Height, 1,000,000 lbs. Static Hook Load

Box on Box Substructure: 29'-6" Height, 25'-6" Clear Height

Setback Capacity: 600,000 lbs.

Racking Capacity: 25,000' (5" Drill Pipe)

Fully integrated, omnidirectional "Walking" system

MUD PUMPS

(3) 1,600 HP Triplex Pumps - 7,500psi

(1) each 1,500 HP AC Motor

ROTATING AND TRAVELING EQUIPMENT

500 ton Canrig 1250 Top Drive w/ 51,400 ft-lbs. torque @ 118 rpm 37-1/2" Rotary Table Independent Drive powered by (1) Hydraulic Motor 500 ton Traveling Block

B.O.P EQUIPMENT

BOP Handling System: Trolly Beam System w/ Hydraulic Winches

13-5/8" x 5,000 psi Annular

13-5/8" x 10,000 psi, Single Ram BOP

13-5/8" x 10,000 psi, Double Ram BOP

2-1/16" X 4-1/16" 10,000 psi Choke Manifold

(1) 7 Station Accumulator Skid

GENERATORS

(4) CAT 3512C Diesel Engines w/ (4) 1750 kVa Generator Sets

(3) Altronic GTI Bi-Fuel (natural gas/diesel) package (1 per engine)**

CONTROL SYSTEM

IEC VFD House

Climate Control Driller's Cabin w/ joystick controls





SHALEDRILLER 303 (continued)

MUD SYSTEM

1000 bbl. Pit System - 7,500 psi

- (3) Hyperpool Shale Shakers
- (1) Atmospheric Degasser
- (1) Mud Gas Separator 1,200 gpm 72" diameter / 23' overall length

MUD MIXING EQUIPMENT

- (3) Chemical Mixing Hoppers
- (1) Caustic Mixing System

LIQUID STORAGE

- (1) 365 bbl. Water Storage Tank
- (1) 385 bbl. Diesel Storage Tank

PIPE HANDLING EQUIPMENT

- (1) ST-80 Iron Roughneck
- (1) Forum Hydraulic Catwalk

ELECTRONIC DRILLING RECORDING EQUIPMENT

MD Totco Recording System and Equipment

DRILL PIPE

25,000' - 5" (S-135) 19.50# w/ NC-50 Connections (30) Joints - 5" HWDP

DRILL COLLARS

(18) 6.5" w/ NC-46 Connections (6) 8" w/ NC-56 Connections

LIVING QUARTERS

- (1) Rig Manager Trailer
- (2) Twelve Person Crew Trailers w/ Change House included